



PRIDE®
MOBILITY
LIVE YOUR BEST®

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039
pridemobility.eu . info@prideeurope.nl

The Baja Bandit is here to push the limits. It's rugged. It's fast. It's uncompromising as a conduit for outdoor adventure. Exactly how Baja Mobility is defined.



9,4" solid tires



Enhanced LED lighting



Designed to be perfect

Specifications

| | |
|--------------------------|--|
| Weight capacity | 181 kg |
| Speed | Up to 12,9 km/h |
| Range per charge | Up to 46,7 km |
| Turning radius | 1347 mm |
| Ground clearance | 113 mm |
| Length | 1260 mm |
| Width | 707 mm |
| Tires | 9,4" solid, front and rear |
| Drive | Rear-wheel drive, sealed transaxle, 36-volt DC motor |
| Weight without batteries | 72,3 kg |
| Batteries | Type: Lithium ion Size: 20 Ah or 40 Ah |
| More? | Download our specifications sheet on the website |

Features

- Most compact 12,9 km/h scooter on the market
- 9,4" Front and rear tires
- Compact frame for easy manoeuvrability and turning radius of only 1347 mm
- Lithium batteries for longer range
- Added suspension for a smooth ride even over rough terrain

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Available colors

