

GO GO[®]

LX WITH CTS SUSPENSION



PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039
pridemobility.eu . info@prideeurope.nl

The Go Go® LX with CTS suspension is a high-quality product with useful features, such as a delta handlebar, a high-placed charging connection, an LED headlight and a spacious basket at the front.



Comfort-Trac suspension



Disassembles into 5 pieces



Modular design for easy serviceability

Specifications

| | |
|--------------------------|--|
| Weight capacity | 136 kg |
| Speed | Up to 7 km/h |
| Range per charge | 3W: Up to 15,3 km 4W: Up to 17 km |
| Turning radius | 3W: 851 mm 4W: 1162 mm |
| Ground clearance | 36 mm |
| Length | 3W: 1010 mm 4W: 1060 mm |
| Width | 521 mm |
| Tires | 3W: 8" solid front and rear 4W: 7" solid front, 8" solid back |
| Drive | Rear-wheel drive, sealed transaxle, 24-volt DC motor |
| Weight without batteries | 3W: 39 kg 4W: 41 kg |
| Batteries | Type: Two 12-volt, sealed lead-acid, non-spillable deep-cycle Size: 12 Ah or 18 Ah |
| More? | Download our specifications sheet on the website |

Features

- Feather-touch disassembly permits simple frame separation with only one hand
- Frame design easily disassembles into 5 lightweight pieces for convenient transport and storage
- Includes 2 sets of easily changeable colored panels in 2 colors – Red and Blue
- Charger XLR port incorporated in tiller allows charging without removing the battery box
- Microprocessor-based controller offers optimal power management and added safety features

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Available colors

