

Jazzy[®] air₂



PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039
pridemobility.eu . info@prideeurope.nl

First impressions happen only once, and the engineers at Pride Mobility considered all the ones you make when they designed the Jazzy Air® 2.



Under-seat storage



Adjustable armrests



Comfort seating

Specifications

| | |
|--------------------------|------------------------------------------------------------------------------|
| Weight capacity | 136 kg |
| Speed | Up to 6,4 km/h |
| Range per charge | Up to 26,7 km |
| Turning radius | 616 mm |
| Ground clearance | 25 mm |
| Length | 1067 mm |
| Width | 590 mm |
| Drive wheels | 10" solid |
| Caster wheels | 6" solid |
| Weight without batteries | 91,5 kg |
| Batteries | Type: Two 12-volt, sealed lead-acid, non-spillable deep-cycle Size: 35 Ah |
| More? | Download our specifications sheet on the website |

Features

- Integrated foot platform with rubber insert and 508 mm of adjustment for comfort in both the elevated and non-elevated positions
- Single-sided caster forks for enhanced maneuverability
- Under-seat front storage compartment keeps your valuables accessible
- Angle, height, and depth adjustable armrests
- Angle height-adjustable headrest

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Available colors

