

GO GO[®] ENDURANCE^{Li}




PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039
pridemobility.eu . info@prideeurope.nl


Dit model biedt alles wat u nodig heeft voor een veilige en zorgeloze reis. Dankzij het standaard 8 Ah lithium accupakket, dat is toegestaan in een vliegtuig, is de Go Go® Endurance ideaal voor lange afstanden.



Verbeterde LED-verlichting



USB oplader



Comfort-Trac-vering

Specificaties

Maximale belasting	147 kg
Snelheid	Tot 6,7 km/u
Maximale actieradius	Tot 21,3 km
Draaicirkel	1225 mm
Bodemvrijheid	36 mm
Lengte	1070 mm
Breedte	521 - 690 mm
Banden	8" massief, voor en achter
Aandrijving	Achterwielaandrijving, 24 volt gelijkstroommotor
Gewicht zonder accu's	41 kg
Accu's	Type: Lithium ion Capaciteit: 8 Ah of 16 Ah
Meer?	Download het specificaties blad op de website

Kenmerken

- Standaard lithium-ion accu van 8 Ah, geschikt voor luchtvaartmaatschappijen, of upgrade naar MAXX-accu van 16 Ah
- Per laadbeurt bereik tot 21,3 km met 16 Ah accu's
- Dankzij de delta-helmstok met ergonomische omhullende handgrepen kunt u de scooter met één hand bedienen en uw polsen laten rusten
- Handige dubbele oplaadpoorten kunnen de accu zowel aan boord als daarbuiten opladen
- Inclusief twee sets gemakkelijk verwisselbare, gekleurde panelen

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Beschikbare kleuren



Granaat Rood